

	Basis unit	Stuurbare probe	Pijp inspectie camera
Item Nr.	TTS-S06-5.5	TTS-S06-5.8 270°	TTS-S06-25.0-20
EAN-Nr.	4.260.153.573.158	4.260.153.573.165	4.260.153.573.172
Monitor			
TFT monitor	3.5"	3.5"	3.5"
Beeld resolutie:	640 x 480	640 x 480	640 x 480
Video Formaat	PAL / NTSC	PAL / NTSC	PAL / NTSC
Camera			
Camera kop diameter	5.5 mm	Ø5.5 mm	Ø25 mm
Probe diameter	5.5 mm	5.8 mm	
Chip type	CMOS	CMOS	CMOS
Camera	628x582 (PAL)	720x576 (PAL)	720x480
Beeldhoek	67 °	67 °	73° / 120°
Beelddiepte	2 ~ 5 cm	2.5~5 cm / max10 cm	5 ~ 60 cm
Video output	NTSC & PAL	NTSC & PAL	NTSC & PAL
Probe lengte	100 cm	100 cm	20 m
IP Klasse	IP67	IP66	IP67
Verlichting	4 LEDs, wit	4 LEDs, wit	12 LEDs, wit
Algemeen			
Data transfer via USB poort:	mini. USB 1.1	mini. USB 1.1	mini. USB 1.1
Batterij	Oplaadbare LI/ION Batterij DC 5V/2A	Oplaadbare LI/ION Batterij 3.7 V/2350 mAh	Oplaadbare LI/ION Batterij 3.7 V/2350 mAh
Max operationele temp unit	-10°C to + 60°C	-10°C to + 60°C	-10°C to + 60°C
Maximum tip temp	-10°C to + 60°C	-10°C to + 60°C	-20°C to + 70°C
Min buig radius	70 ~100mm	70 ~100mm	45 ~ 70mm
Articulatie	Geen	2-weg Links > 135° Rechts > 120°	Buigbare camera tube
Verbruik max	450mA (w/o LED)	450mA (w/o LED)	500mA (w/o LED)
Gewicht	ongeveer 350 g	Ongeveer 635 g	4kg
Frame rate:	30 fps (frames/sec)	30 fps (frames/sec)	30 fps (frames/sec)
Foto	628x582 (PAL)	640x480 (PAL)	628x582 (PAL)
Opname	640x480 (307.200 pixels)	640x480 (307.200 pixels)	640x480 (307.200 pixels)
MJPG formaat	AVI	AVI	AVI
SD slot supports Micro SD	max 4 GB SD card	max 32 GB SD card	max 32 GB SD card
Micro SD card incl.	SD card 2 GB	SD card 4 GB	SD card 4 GB
Zoom Maximum	2x	2x	2x
Talen	EN, DE, FR, ES - 16 langues	EN, DE, FR, ES - 15 langues	EN, DE, FR, ES - 16 languages
Prijs	€ 525,00	€ 1.020,00	€ 1.450,00